



LiftMaster[®] STAR1000 Receiver with Security+ 2.0[™] technology represents the next generation of LiftMaster Radio Access Controls that delivers 2x the range and greater transmitter capacity.

LiftMaster's STAR1000 access solution allows the management of multiple access points, like gate and parking application remote control needs.

STAR1000's individual and bulk programming process simplifies the coding of large quantities of remote controls.



Commercial Access Control Receiver Model STAR1000

- High-capacity Receiver for Gate and Commercial Door Operators.
- Security+ 2.0[™] technology.
- Full keypad programming with LCD screen.

STAR1000



STAR1000

COMMERCIAL ACCESS CONTROL RECEIVER

Standard Features:

- Security+ 2.0[™] technology provides 2x the radio range of standard remotes.
- Compatible with Homelink Wireless Control System.
- 1000 remote capacity to support large quantity remote control requirements.
- Single and block addition.
- Supports suspending and unsuspending of remote controls to withhold and reinstate access.
- Designed for outdoor environments.
- Duplicate memory module included that may be removed for programming additional receivers or for safe storage.
- 9" antenna included.

Ordering Guide

Passport Remote Controls

Model PPV1*	Description Passport 1-Button Remote Control
PPV3*	Passport 3-Button Remote Control
PPK1*	Passport 1-Button Mini Remote Control
PPK3*	Passport 3-Button Mini Remote Control
PPK1PH*	Passport 1-Button Mini Proximity Remote Control
PPK3PH*	Passport 3-Button Mini Proximity Remote Control
PPLV1**	Passport Lite 1-Button Remote Control
PPLK1**	Passport Lite 1-Button Mini Remote Control
PPLK1PH**	Passport Lite 1-Button Mini Proximity Remote Control

Accessories 86LM

Remote Antenna Mounting Kit

*Available as a single pack and 10 pack \mid **Available as a 10 pack and 100 pack



The Chamberlain Group, Inc. • 845 Larch Avenue • Elmhurst, IL 60126 www.LiftMaster.com

ISO 9001 Certified Manufacturer

SPANISH AND FRENCH VERSIONS ARE AVAILABLE ONLINE



Follow us on Facebook, Twitter and YouTube!





Receiver Specifications

Power

9-30 VAC and 9-34VDC

Relay Output Type One Form A Relay Contact. Common and Normally Open Contacts

Operating Temperature -40 to 60 degrees C

Storage Temperature -40 to 85 degrees C

Warranty 1 year

Security+ 2.0[™] Remote Controls

Model Number	
811LM	1-Button Encrypted DIP Remote Control
813LM	3-Button Encrypted DIP Remote Control
890MAX	3-Button Mini Remote Control
893MAX	3-Button Remote Control
895MAX	3-Button Premium Remote Control
877MAX	Keyless Entry

Dimensions

DASMA



I.C./F.C.C. Certified

ƏIDA

©2013 LMACCA1000 1/13 The Chamberlain Group, Inc. Printed in U.S.A.